



SLD / BLD SERIES AIR HANDLERS



THE ALLSTYLE SLD AIR HANDLER

DEDICATED DOWNFLOW
SIX MODELS 600 TO 1600 CFM
1.0 TO 4.0 TONS OF COOLING

THE ALLSTYLE BLD AIR HANDLER

DEDICATED DOWNFLOW
FOUR MODELS WITH 1200 TO 2000 CFM
2.5 TO 5.0 TONS OF COOLING

STANDARD FEATURES

DOWNFLOW APPLICATION ONLY
FULLY INSULATED CABINETS ARE
FORMED OF PAINTED GALVANIZED STEEL
MULTI-SPEED PSC MOTORS
DUAL CIRCUIT ELECTRICAL PROTECTION
OF 15 & 20 KW MODELS
TD RELAY & CONTROL TRANSFORMER
PREWIRED FOR HEAT PUMP APPLICATION
208/230 VOLT 60 HERTZ

OPTIONAL ACCESSORIES

ELECTRIC HEAT
3,5,6,8,10,15, OR 20 KW

FACTORY INSTALLED
EXPANSION VALVE OR CHECK
& EXPANSION VALVE FOR
HEAT PUMP APPLICATIONS

FACTORY ELECTRIC DISCONNECT
(MODELS W/ 10 KW AND UNDER)

Physical Dimensions (Inches)					
Model	Width	Depth	Height	Supply Air Opening W x D	Return Air Opening W x D
SLD	19.5	19.25	45.5	17.5 x 15	18 x 14.5
BLD	22.5	22.25	51.5	19 x 18.5	21 x 18.5
Specifications may change without notice					



SLD / BLD SERIES AIR HANDLERS

ELECTRICAL RATINGS : 240 VOLTS : 60 HERTZ : SINGLE PHASE

MODEL	KW @ 240 VAC	BTUH	TOT AMPS	MCA CKT1	MCA CKT2	MOP CKT1	MOP CKT2
SLD12/18/24/30-0	0	0	1.45	2	0	15	0
SLD12/18/24/30-3	3	10,257	14	17.1	0	20	0
SLD12/18/24/30-5	4.8	16,411	21.45	26.8	0	30	0
SLD12/18/24/30-6	6	20,512	26.45	33.1	0	40	0
SLD12/18/24/30-8	8	27,352	34.75	43.5	0	50	0
SLD12/18/24/30-10	9.6	32,822	41.45	51.8	0	60	0
SLD12/18/24/30-15	14.4	49,234	61.7	51.8	25	60	30
SLD/BLD36-0	0	0	2.7	3.4	0	15	0
SLD/BLD36-3	3	10,257	15.2	19	0	20	0
SLD/BLD36-5	4.8	16,411	22.7	28.4	0	30	0
SLD/BLD36-6	6	20,512	22.7	34.6	0	40	0
SLD/BLD36-8	8	27,352	36	45	0	50	0
SLD/BLD36-10	9.6	32,822	42.7	53.4	0	60	0
SLD/BLD36-15	14.4	49,234	62.7	53.4	25	60	30
SLD/BLD36-20	19.2	65,649	82.7	53.4	50	60	60
SLD/BLD42/48-0	0	0	4	5	0	15	0
SLD/BLD42/48-3	3	10,257	16.5	20.6	0	20	0
SLD/BLD42/48-5	4.8	16,411	24	30	0	30	0
SLD/BLD42/48-6	6	20,512	29	36.3	0	40	0
SLD/BLD42/48-8	8	27,352	37.3	46.7	0	50	0
SLD/BLD42/48-10	9.6	32,822	44	55	0	60	0
SLD/BLD42/48-15	14.4	49,234	64	55	25	60	30
SLD/BLD42/48-20	19.2	65,649	84	55	50	60	60
BLD60-0	0	0	5	6.3	0	15	0
BLD60-3	3	10,257	17.5	21.9	0	20	0
BLD60-5	4.8	16,411	25	31.3	0	30	0
BLD60-6	6	20,512	30	37.5	0	40	0
BLD60-8	8	27,352	38.3	47.9	0	50	0
BLD60-10	9.6	32,822	45	56.3	0	60	0
BLD60-15	14.4	49,234	65	56.3	25	60	30
BLD60-20	19.2	65,649	85	56.3	50	60	60